

Product Data Sheet



LF 125kHz ISO Card RFID Tag

Overview

A low frequency (LF) Proximity ISO card, flexible Card design to suit most 125 kHz proximity systems. Contactless power supply, very low power passive RFID tag operating at 125kHz.

This passive tag offers good performance in the presence of metals and liquids and other non-conducting materials, allowing tag operation in very difficult or harsh environments.

LF RFID systems are widely used for a wide variety of data collection and identification applications.

Full credit card sized product for ticketing and access control applications. Excellent printing possibilities, can be printed on either side of the card.

Dimension and tolerances are in accordance with ISO standard.

Applications

- Building access control
- Loyalty cards
- Customer loyalty programs
- Ticketing for recreational venues
- Time & attendance
- Ticketing for public transport

Tag

RF Frequency	125kHz
Chip	Unique
Memory	64bit Read Only Memory

Physical

Size	85.6mm x 53.98mm
Material	PVC

LF 125kHz ISO Card RFID Tag

Part No: EUR111T2379

Avonwood Developments Ltd.

Knoll Technology Centre, Stapehill Road, Wimborne, Dorset, BH21 7ND

tel: +44 (0)1202 868000 fax: +44 (0)1202 868001

email: sales@avonwood.co.uk web: www.avonwood.co.uk

